

SOLO & DUO SPECIFICATION			
	SOLO	DUO	
Max Power Consumption	10W	10W	
Cartridge Support	Moving Magnet	Moving Magnet/Moving Coil	
Gain @ 1kHz	39dB	39dB	60dB
Nominal Output	300mV	300mV	300mV
Sensitivity for Nominal Output	3.35mV	3.35mV	3.05uV
Equivalent Input Noise (A-Weighted)	~0.09uV	~0.09uV	~0.08uV
RIAA Curve Accuracy	+/- 0.65dB 30Hz-20kHz	+/- 0.3dB 30Hz-50kHz	
Signal to Noise Ratio Grounded Inputs ref. 1V output (20Hz-20kHz BW)	>90dB	>90dB	>70dB
THD+N 1kHz (20-20kHz BW)	<0.0025%	<0.0025%	<0.020%
Input Impedance	47k Ω	47k Ω	100 Ω
Input Capacitance	100pF	100pF	100pF
Overload Margin	>30dB	>30dB	>30dB
Crosstalk @10kHz	>85dB	>85dB	>75dB
Dimensions (HxWxD)	48mm x176mm x132mm (1.9x6.9x5.2")	48mm x215mm x159mm (1.9x8.5x6.2")	
Weight	0.68kg (1.5lbs)	0.95kg (2.1lbs)	